



Order form
Orderer

Valid from 09.05.2011
Order no.

CL31 Lidar Ceilometer

Vaisala Ceilometer	CL31	C	1	1											1	PRICE
Operating voltage	100-115 VAC	1														
	230 VAC	2														
<i>Reserved</i>		C														
CSP Model	No		1													
	<i>CL31-BL (with aerosol settings)</i>		A													
	<i>CL31-cETL (for Canadian markets)</i>		B													
Data line interface	RS232			A												
	RS485			B												
	<i>Modem (DMX501 modem module)</i>			C												
<i>Reserved</i>			1													
Software	Standard			A												
	<i>Standard + Sky Condition</i>			B												
Cable Termination	No						1									
Box	<i>Box with additional transient protection (Termbox-1200)</i>						2									
	<i>Box without additional transient protection (CLTERMBOX)</i>						3									
Bird deterrent device	No							A								
	<i>Bird deterrent device (CL31BIRDKIT)</i>							B								
Optical Termination	No						1									
Hood	<i>Needed for indoor service (CLTERMHOOD)</i>						2									
Service Cable	No							A								
	<i>RS cable for local maintenance access (QMZ101)</i>							B								
	<i>USB cable for local maintenance access (CL31USBCABLE)</i>							C								
Application Software	No						1									
	<i>CL-VIEW Cloud Reporting Software for Ceilometers</i>						2									
	<i>BL-VIEW Boundary Layer Software for Ceilometers</i>						3									
Shock Absorber	No							A								
	<i>CT35022, recommended for marine and off-shore installations</i>							B								
Internal Humidity	No												1			
Transmitter	<i>Humidity transmitter (CLHUMITTER)</i>												2			
Radio Modem Kit	No													A		
	<i>Attachment mechanics for radio modem antenna (CLRADIOKIT)</i>													B		
<i>Reserved</i>														1		
Manual language	No manual														A	
	English														B	
	French														C	
TOTAL																
QTY																
TOTAL VALUE																

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

CL31	2	C	1	A	1	A	2	A	1	B	1	A	1	A	1	B
------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

End customer: _____

Recommended accessories:

Accessory
Drilling template
cETL testing procedure for 1 to 15 units

Code
CT45182
CETLTESTING-CL